



PRIMAVERA 125/150 COLOR VIBE - TECHNICAL SPECIFICATIONS

MOTOR	3-valve 4-stroke single cylinder i-get catalysed
CILINDRADA	124 cc (155 cc)
DIÁMETRO X CARRERA	52 mm x 58,6 mm (58 mm x 58,6 mm)
POTENCIA MÁXIMA	8,1 kW - 11 HP - a 8,000 rpm (9,2 kW - 12,5 CV- 7,750)
PAR MÁX	10.4 Nm at 6,750 rpm (12.4 Nm a 6,750 rpm)
CONSUMO	40 km/l (37 km/l)
CO2	60 g/km (63 g/km)
SISTEMA COMBUSTIBLE	Electronic Injection
ENFRIAMIENTO	Forced air
START	Electric
CAJA DE CAMBIOS	CVT automatic with torque server
EMBRAGUE	Automatic dry centrifugal with shock absorbers
ESTRUCTURA DE CARGA	Sheet steel shell with welded structural reinforcements
SUSPENSIÓN FRONTAL	Single arm with helical spring and hydraulic shock absorber
SUSPENSIÓN TRASERA	Helical spring with adjustable preload (4 positions) and single hydraulic shock absorber
FRENO DEL.	Stainless steel Ø 200 mm disc with hydraulic control
FRENO TRAS.	Ø 140 mm drum with mechanical control
ABS/ASR	ABS at the front wheel only
NEUMÁTICO DELANTERO	Tubeless 110/70 - 12"
NEUMÁTICO TRASERO	Tubeless 120/70 - 12"
LARGO/ANCHO/DISTANCIA ENTRE RUEDAS	1.870 / 735 / 1.340 mm
ALTURA ASIENTO	790 mm
DEPÓSITO	8 litres
HOMOLOGACIÓN	Euro 5